






TECHNICAL DATA SHEET - CST 0850/01 - 23/07/2003

GF 7676

(*)				
T	°C	-100 / +250		
p	bar		250	50
V	m/s		3	25
pH		3 + 12		

(*) Avoid the product's use at the maximum temperature and pressure associated values without consult the manufacturer

Composition

- Aramid yarns
- GFO® GORE yarns

Features

Gland packing manufactured with GFO® GORE and Aramid yarns with a particular braiding process which brings separately and alternatively each section made by a single yarn (zebra design). This design increases the resistance to extrusion and preserves the shaft's wear.

Applications

Gland packing for centrifugal and reciprocating pumps, agitators, mixers, suitable with the main industrial fluids and water.

size mm	size inch	kg/box	lbs/box	mt/box	ft/box	mt/kg	ft/lbs
3,0	1/8	1,0	2,2	74,1	243	74,1	110,3
4,0	-	1,0	2,2	41,7	137	41,7	62,1
5,0	3/16	1,0	2,2	26,7	87	26,7	39,7
6,0	-	2,5	5,5	46,3	152	18,5	27,6
6,5	1/4	2,5	5,5	39,4	129	15,8	23,5
8,0	5/16	2,5	5,5	26,0	85	10,4	15,5
9,5	3/8	2,5	5,5	18,5	61	7,4	11,0
10,0	-	2,5	5,5	16,7	55	6,7	9,9
11,0	7/16	2,5	5,5	13,8	45	5,5	8,2
12,0	-	2,5	5,5	11,6	38	4,6	6,9
12,7	1/2	2,5	5,5	10,3	34	4,1	6,2
14,0	9/16	5,0	11,0	17,0	56	3,4	5,1
16,0	5/8	5,0	11,0	13,0	43	2,6	3,9
17,5	11/16	5,0	11,0	10,9	36	2,2	3,2
18,0	-	5,0	11,0	10,3	34	2,1	3,1
19,0	3/4	5,0	11,0	9,2	30	1,8	2,8
22,0	7/8	5,0	11,0	6,9	23	1,4	2,1
25,5	1	5,0	11,0	5,1	17	1,0	1,5

Packaging could be +/- 10 % in weight.

Customized sizes and packaging are available on demand.